

SPECIFICATION

Electronic Version 1.2.8

Stylesheet Version 1.0

Tracing the execution path of a computer program

Background of Invention

- [0001] Field of the Invention
- [0002] The present invention relates to tracing, and more particularly to tracing the execution path of a computer program.
- [0003] Background of the Invention
- [0004] Computers have proliferated into all aspects of society and increasingly form the backbone of large organisations. When a computer system fails to respond as intended, businesses are invariably unable to provide even the most basic of services. Money, reputation or even lives may be lost, dependant upon the criticality of the service, the outage time etc.
- [0005] In today's increasingly competitive marketplace, quality is of the utmost concern. Users' expectations are high and thus the reliability of hardware/software is especially important. Customers do not tolerate mistakes and the later a defect is discovered, the more costly it can prove to the manufacturer.
- [0006] Typically therefore, software developers implement a rigorous testing regime in order to ensure that a product or system is fully operational and consistently performs according to its functional specification, before it is made available to the public.
- [0007] Software development is however an increasingly complex process. Even using the most rigorous techniques, software developed by people will suffer failures.

Most software developers understand this and therefore accept the need to be able to effectively diagnose the cause of such a software failure.

[0008] A most effective technique is known as "tracing". In this technique a program records ("traces") important information that can be used for further analysis after the occurrence of a software failure. Figure 1 is a component diagram of a computer system performing tracing according to the prior art. A computer system 10, runs an operating system (o/s) 20, which could for example be Windows NT available from Microsoft Corporation. A program 30 executes on top of operating system 20 and may consist of a number of separate modules (not shown), each defining separate functionality. As program 30 executes, it calls various trace functions 40 which are used to record certain information in a trace log 50. Note, although the log is shown as present on the same computer system, computer system 10 may in fact be connected to another machine across a network (neither shown) and the trace log may instead reside on that machine.

[0009] Tracing typically occurs at three stages in the processing or executing of a program. These stages are known as the "entry", "exit" and "exception" points of tracing.

[0010] The "entry" trace information is gathered when a module obtains control from another module. The information recorded is normally the input values provided to the module.

[0011] The "exit" trace information is gathered when a module returns control to a module from which it has previously received control. The information recorded is normally the output values returned to the module from which it obtained control in the first place.

[0012] The "exception" trace information is gathered whenever an extraordinary or interesting event occurs within a module after it has been entered but before it has returned control to the module from whom it originally received control. The information gathered is normally information that relates to the exceptional condition that has occurred.

[0013] As previously mentioned the entry, exit and exception information is outputted to a trace log. Upon the occurrence of a software failure, a software developer can analyse the trace information in this log. This information can then be used to determine which modules were called and what information was passed between them, including any interesting events that have occurred. This hopefully allows the developer to understand and locate the source of the error and fix it.

[0014] Figure 2 shows entry, exit and exception tracing according to the prior art. A program 100 consists of two modules, "Main" 105 and "Function" 110. The program runs on an operating system 120 which initially passes control to Main. Main receives two parameters, p1 and p2 as input. These may be specified by the user from the command-line or be the result of output from another program / module (not shown). Main calls a trace_in function to record entry trace to trace log 130, and a trace_out function to record exit trace to trace log 130.

[0015] Trace_in is passed three parameters, "Main", p1, and p2. "Main" is used as an identifier in the trace log such that the values of p1 and p2 can be connected with module Main. It can be seen from the log that parameters p1 and p2 have values of 1 and 3 respectively upon entry to Main. Control is then passed to module FUNCTION 110, which passes parameters p3 and p4 as parameters. FUNCTION performs a trace_in on both p3 and p4, which are identified by the heading "FUNCTION" in trace log 130. It can be seen that p3 has a value of 2 and p4 has a value of 4 upon entry to the module FUNCTION.

[0016] A trace_data function writes extraordinary events / events of interest to the trace log. It passes an identifier "FUNCTION" and the data to be read out DATA1, or a number of parameters. This is exception trace.

[0017] Module FUNCTION ends and a trace_out function is called passing it the "FUNCTION" identifier, along with parameters p3 and p4. Note, the dotted lines connecting the various trace functions represent calculations and processing performed by the program but not shown (i.e. additional program instructions). It can be seen from trace log 130 that such program instructions have manipulated p3 and p4 such that their values have changed from those initially recorded at

trace_in. P3 now equals 5 and p4 equals 2.

[0018] As previously mentioned, exit information (via the trace_out function) is recorded prior to a module relinquishing control to the module which originally called it. In this example control is returned to Main 105, additional processing performed (dotted lines) and the trace_out function called. It is passed the "Main" identifier, along with p1 and p2. The trace log once again shows that additional program instructions have manipulated p1 and p2 such that their values are now 4 and 1 respectively. Control is then returned to operating system 120.

[0019] Tracing, typically occurring at entry, exit and exception, has a very coarse granularity. It provides very little information as to the path followed during program execution. It is possible to obtain a reasonable level of detail by calling the trace_data function on a regular basis (or whenever anything unusual happens (e.g. the value of a particular parameter is not as expected)), but this is expensive in terms of CPU time. Even on the OS/390 systems (available from IBM Corporation), in which trace information is dumped to fast volatile memory, performance is degraded by approximately 50%. For this reason customers often cannot afford to leave trace running continuously. Thus when a software failure occurs, the operating system often provides call hierarchy (i.e. which modules were called during program execution) but does not provide any more information than that. Time is lost because, trace then has to be turned on and the failure simulated before diagnostics can begin. Customers do not expect these sort of delays. In their eyes, software that they've paid good money for is not supposed to fail.

[0020] Not only is tracing expensive in terms of CPU performance, but hand-instrumenting a program with trace instructions is a time consuming job. Knowing the most appropriate points at which to place trace_data statements also requires experience. Trace_in and trace_out statements, on the other hand, always go at the beginning and end of a module respectively.

[0021] Even when all the appropriate trace information is captured in a trace log, this information can be difficult to extract. When a module completes, it is only possible to determine which processing occurred within the module by searching

for the previous entry trace for that module and examining all the trace entries that this module may have called. This is exceptionally tedious, especially if the flow of control through modules is complex. The situation may be further complicated in a multi-user system where trace records for multiple activities are traced at the same time.

[0022] Figure 3 shows tracing in a multi-user system according to the prior art. A computer system (not shown) runs a Process 1. This includes three program modules A, B and C, each with trace_in and trace_out function calls. Trace Log 150 shows the trace information outputted by process 1. It can be seen that trace_in (ti) is called for all modules. Trace_out (to) is then called for module C. Note, although not shown, the log will in reality contain parameter values for each trace function call (see figure 2).

[0023] Before trace_out can be called for modules B and A (in that order), process 2 is started. Process 2 also includes three modules, A, B and C, each calling the trace_in and trace_out functions. Thus process 2 dumps the trace_in parameter values for module A out to log 150. This entry fills up the log. New information is thus written to the beginning of the log (shown by the circular arrows). Trace Log 150' shows what happens next. Process 2 runs faster than process 1 and thus it continues to write to the trace log 150' from the top. Process 2 thus outputs trace_in information for its module B, and C. It also dumps trace_out information for its modules C and B. Obviously both processes have not finished outputting information to the trace log 150', but it can be seen that at this point in time all the trace information above the dotted line in trace log 150 for process 1, has been overwritten by process 2. Thus in the event of a software failure, log 150' provides very little help in diagnosing the execution flow taken by process 1. Note, Processes 1 and 2 may be on the same machine or on separate machines.

Summary of Invention

[0024] Disclosure of the Invention

[0025]

Accordingly, the invention provides a method for tracing the execution path of

	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

[0026] Preferably, the storage area is in volatile memory and the contents of the storage area is output to non-volatile memory (e.g. a file or trace log) at a predetermined point in time. Alternatively, the storage area itself is non-volatile memory.

[0027] In the preferred embodiment trace information is output to the trace log upon exit from the at least one module and the contents of the storage area is output at the same time. Thus the log contains a record of the values of any specified parameters upon exit from the at least one module, as well as a record of the execution path taken through that module.

[0028] Since the exit record is the most recent trace record to be written, it is preferably possible to determine the flow through the module even if this is the only trace record available (i.e. the only record that has not been overwritten). Thus the problem addressed with reference to figure 3 is addressed. Furthermore, because the contents of the storage area is preferably outputted as one record, it is easy to extract the information from the trace log. The trace log may consist of multiple trace entries interwoven with trace entries from other systems. According to the preferred embodiment, one can easily extract the relevant entry as all the information is held on the one line.

[0029] Alternatively, the contents of the storage area is output to the log when the storage area is determined to be full. As yet another alternative, the contents of the storage area is output to the log upon the occurrence of a failure within the program.

[0030] In all cases customer satisfaction is increased because the information contained within the storage area can be used to diagnose problems more quickly. The information provides a much greater level of detail than previously possible. It indicates the execution path or flow followed through a program and is especially useful when the program being traced is complex. It provides a valuable insight into the behaviour of the program at run-time.

[0031] According to the preferred embodiment, the cost of pushing a unique identifier into the storage area upon execution of a particular set of program instructions is trivial. Thus customers can afford to run with trace on continuously so that important problem diagnostics information can be collected in real-time.

[0032] Preferably, when the last available space in the storage area has been written, old identifiers are overwritten from the beginning of the area with new values. Thus the storage area can be of a limited size and does not consume an unnecessary amount of resources. A sensible size for the storage area depends upon the complexity of the program being traced.

[0033] According to the preferred embodiment, the storage area stores the position at which the last unique identifier was written. Thus it is possible to determine the number of unique identifiers that have been overwritten in the circular storage area, before being outputted to the trace log. If this number is excessively large, the size of the storage area is preferably increased.

[0034] In a further aspect, the invention provides an apparatus for tracing the execution path of a computer program comprising at least one module including a plurality of instructions, at least one of said instructions being a branch instruction, said apparatus comprising: means for identifying each branch instruction; means for evaluating each branch instruction to be one of true and false; and means, responsive to an evaluation of true, for pushing a unique identifier into a predefined area of storage, wherein said unique identifier is associated with the instructions executed as a result of said evaluation of true.

[0035] In a yet still further aspect, the invention provides a method for instrumenting

100150-025350

a computer program comprising at least one module including a plurality of instructions, at least one of said instructions being a branch instruction, each branch instruction being evaluated to be one of true and false at run-time, with at least one signature instruction for indicating the execution path of said program at run-time, the method comprising the steps of: identifying each branch instruction; identifying the instructions associated with an evaluation of true at run-time; instrumenting said instructions associated with an evaluation of true with a signature instruction, wherein said signature instruction causes a unique identifier to be pushed into a predefined area of storage upon execution of said true instructions at run-time.

[0036] According to the preferred embodiment, little experience is required to hand-instrument the code, since such signature instructions are always associated with a branch instruction. This is unlike the placing of trace_data statements, which do require more experience. Preferably, it is only as a result of a branch instruction that the execution flow changes. Otherwise, each instruction is executed on a line by line basis.

[0037] According to another aspect, the invention provides a compiler for instrumenting a computer program comprising at least one module including a plurality of instructions, at least one of said instructions being a branch instruction, each branch instruction being evaluated to be one of true and false at run-time, with at least one signature instruction for indicating the execution path of said program at run-time, said compiler comprising: means for identifying each branch instruction; means for identifying the instructions associated with an evaluation of true at run-time; means for instrumenting said instructions associated with an evaluation of true with a signature instruction, wherein said signature instruction causes a unique identifier to be pushed into a predefined area of storage upon execution of said true instructions at run-time.

[0038] According to the preferred embodiment, automatically instrumenting a program with signature instructions greatly eases the job of the software developer. Detailed program execution flow can be obtained, without the time

consuming task of modifying the code by hand.

Brief Description of Drawings

- [0039] A preferred embodiment of the present invention will now be described, by way of example only, and with reference to the following drawings:
- [0040] Figure 1 is a component diagram of a computer system performing tracing according to the prior art;
- [0041] Figure 2 shows entry, exit and exception tracing according to the prior art;
- [0042] Figure 3 shows tracing in a multi-user system according to the prior art;
- [0043] Figures 4 and 5 illustrate tracing according to a preferred embodiment of the present invention.
- [0044] Figure 6 shows the process of outputting signature information at the first point of failure according to a preferred embodiment of the present invention; and
- [0045] Figure 7 shows the operation of a compiler in accordance with a preferred embodiment of the present invention.

Detailed Description

- [0046] Description of the Preferred Embodiments
- [0047] Figures 4 and 5 should be read in conjunction with one another. Figure 5 shows a sample program, "test program", from which execution information is gathered at run-time according to a preferred embodiment of the present invention. Figure 4 is a flow chart illustrating how the sample program executes in accordance with the preferred embodiment.
- [0048] Upon execution of the program, a small, fixed size area called a signature area 300 is defined (step 200). In the example, the signature area may contain up to eight signature points 310 (define sig_area size(8)).
- [0049] Each signature point comprises a unique 4 bit identifier (number). This identifier is, according to the preferred embodiment, used to indicate the

execution path or flow followed through the program.

- [0050] Typically a program executes each instruction line by line, until a decision point or branch instruction is reached. It is at such a point that the program may jump to a specified piece of code (set of instructions) or else ignore that code and continue with subsequent instructions. One example of a branch instruction is an "if statement" (found in most programming languages):

```
if condition = TRUE
do
  instruction 1
L1: instruction 2
J1: end do;
[else
do
```

- [0051] It can be seen from the above that either instructions 1 and 2 are executed, or instruction 3 alone, dependant upon whether "condition" = TRUE or FALSE. There are many other examples of branch instructions (e.g. case tests / statements found in the C programming language) and it is at such points that it is helpful to capture execution flow information. The signature area 300 holds this information.

- [0052] At step 210 of figure 4, the signature area is initialised to 0 (set sig_area=0) (not shown in figure 5). In this example, the trace_in function is called as before (step 220), although this does not have to be so. Note, trace_in is passed one or more parameters as previously explained (not shown in figure 5).

- [0053] In the example, the program then loops until a condition evaluates to TRUE (step 230), at which point the program calls the trace_out function (step 280). This function also accepts parameters as previously discussed (not shown). Whilst however the condition evaluates to FALSE, the logic between "repeat until..." and "end repeat" is performed. In the example, this logic consists of a number of case statements (branch instructions). A case statement is a Boolean test. In the example, the first case statement evaluates to TRUE when a parameter (not shown)

= 1, the second case statement evaluates to TRUE when another parameter (not shown) = 2, and so on. An evaluation of TRUE results in the code forming part of the current case statement being executed, otherwise the next case statement is evaluated. Thus it will be appreciated that the execution flow through the program will vary dependant upon the evaluation of each case statement.

[0054] Thus in accordance with figure 4, a case statement is evaluated (step 230). If it evaluates to FALSE, then step 270 checks for another case statement. If there aren't any, then step 230 evaluates the original condition. The program then either loops round again or outputs trace at step 280.

[0055] If on the other hand, a case statement evaluates to TRUE at step 240, then an identifier is pushed into the signature area at step 250 (e.g. push 1 into sig_area). Although in the example, this identifier is hard-coded, this need not be the case. The hard-coded numeral may, for example, be replaced with a variable, initially set to 0 and then incremented each time a push into the signature area is made. A pointer 320 keeps note of the current position in the signature area. Having pushed a unique identifier into this signature area, the pointer is incremented at step 260.

[0056] According to the preferred embodiment, signature points are added into the signature area from left to right (Note, this does not have to be the case and other variations are considered within the spirit of the invention). In the example, the seven most recent signature points are held in the signature area. These are used to track the execution flow through the program. The purpose of the last element 330 will be explained later.

[0057] In the example, case statement 1 is evaluated to TRUE first such that 1 is pushed into the signature area. Execution then jumps to case statement 4 (i.e. case statements 2 and 3 evaluate to false)(arrow 1); case statement 2 (arrow 2); case statement 3 (arrow 3); case statement 1 (arrow 4); and finally case statement 2 (arrow 5). It can be seen that the corresponding identifiers have been pushed into the signature area (1; 4; 2; 3; 1; 2). These numbers indicate which set of instructions have been executed at run-time and in what order.

[0058] According to the preferred embodiment, when the program or module finishes, trace is output to trace log 340 as before (step 280). Additionally the information contained within the signature area is also output to the trace log (step 290). The signature information provides valuable insight into the behaviour of the program. Should the program fail or behave erroneously, then the signature points can be used in subsequent problem diagnostics.

[0059] According to the preferred embodiment, once the signature area 300 is full, old signature points are overwritten. Note, according to the preferred embodiment signature information is only written out to the trace log along with a trace exit record (i.e. at the end of the module/program). If a module/program is particularly complex, then the signature area may not be large enough. Thus signature points may be overwritten before they are recorded in the trace log. The last element 330 holds the number of the last signature point that is written (6). It is possible to determine from this number how much signature information is missing as a result of being overwritten. For example, if a signature point is written into element 7, this fills the signature area. A subsequent signature point is thus written into the first element of the signature area. Last element 330 is then updated to read 1. It is thus possible to determine that the first element in the signature area has been overwritten before being outputted to the trace log (i.e. it is possible to determine that this information is missing). If a large number of signature points are continually overwritten before being recorded in the trace log, then a larger signature area can be defined. In an alternative embodiment, the signature information is written straight out to the trace log every time the signature area is filled.

[0060] For many modules it is sufficient to have a small number (e.g. 15) of signature points and a signature area limited to 32 bits (i.e. 4 bits per signature point, making 8 signature points). The push operation usually becomes two low-level instructions (a SHIFT followed by an OR). Therefore, for all practical purposes, the implementation cost is negligible. Even for larger signature areas and more signature points, a trivial marginal processing overhead is required. Thus a simple and efficient determination of module processing is provided. As a result,

customers can afford to run with a more detailed trace (i.e. than that provided by the trace_in and trace_out functions) on continuously.

[0061] As previously mentioned, according to the preferred embodiment, the signature information is always written out with the exit trace record (i.e. the trace_out data). Since the exit trace record is the most recent trace record to be written, it is possible to determine the flow through the module even if this is the only trace record available (i.e. the only record that has not been overwritten). Thus the problem discussed with reference to figure 3 is addressed.

[0062] In an alternative embodiment, the signature information is outputted to the trace log at the point of failure (see figure 6). This is useful in the situation where a failure causes the program/module to loop indefinitely and thus never output that extremely helpful exit record. Furthermore, customer satisfaction is increased since problems can be diagnosed much more quickly. There is no need to instrument the program with the more detailed trace_data statements, which takes time and experience. Instead data is captured upon a first failure and technicians can set about solving the problem immediately. Of course outputting the signature information also increases customer satisfaction because it too decreases the time taken to solve a software failure.

[0063] In one embodiment a program's code is hand-instrumented with instructions that enable a signature point to be pushed into the signature area. Note, as previously mentioned, such signature points are preferably only required at points where the code branches. Thus less experience is needed to determine where to place the signature points. This is unlike the placing of the trace_data statements, which do require more experience. According to an alternative embodiment, the code is automatically instrumented with such instructions at compile-time.

[0064] Figure 7 shows the operation of a compiler in accordance with a preferred embodiment of the present invention. A compiler 410 is provided with a program's source code 400 as input. The compiler processes this source code to produce object code 420. A listing of the source code 415 can also be produced at this stage. The object code is then passed to a linker 430 which uses this code 420 to

produce an executable 440.

[0065] Typically, there are three stages to the compilation process: lexical analysis; syntax analysis; and code generation. During the lexical analysis, symbols (e.g. alphabetic characters) are grouped together to form tokens. For example the characters P R I N T are grouped to form the command (token) PRINT. In some systems, certain key words are replaced by shorter, more efficient tokens. This part of the compilation process also verifies that the tokens are valid. Next, the syntax analyser checks whether each string of tokens forms a valid sentence. Finally, the code generation stage produces the appropriate object code.

[0066] The syntax analyser is able to identify branch instructions in a program's source code. According to the alternative embodiment, the compiler is modified to instrument the code with instructions for pushing a signature point into a defined signature area after each occurrence of a branch instruction. By allowing the compiler to automatically instrument the code at compile-time, the job of the software developer is greatly eased. Detailed execution flow information can be obtained, without the time consuming task of modifying the code by hand. Preferably, the compiler also instruments the code with an instruction to define the size of the signature area and an instruction to write the signature information out to a trace log at the appropriate point (any one of those discussed above).

[0067] According to the alternative embodiment, source code is compiled with one or both of two compiler switches set. The first switch determines whether the code is automatically instrumented with signature points or not, and the second switch allows a user to modify the size of the signature area. If the program being traced is particularly complex, then the size of the signature area may need to be increased.